

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	25
Ratio (i=)		56
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	0.55
Service factor		1
Rated Power P1	[kW]	0.54

Output data

Gear unit **M RS 60 PC 56 80 B14 AC 25 MT 0.55 kW 80 A4 B14 X3 B3**

Type		RS - Worm speed reducers
Input type		M
Size		60
Ratio (i=)		56
Input flange		B14
Mounting position		B3
Input speed	[rpm]	1400
Output speed	[rpm]	25
Rated output torque	[Nm]	126.06
Service Factor		1
Efficiency		0.6
Inertia moment	[kgm ²]	0.000104

Gear unit configuration

Output shaft	Hollow output shaft
Fixing	Shaft mounting
Version	PC

Output radial and axial loads

Ball bearings output radial load	[N]	4600
Taper bearings output radial load	[N]	6100
Ball bearings output axial load	[N]	920
Taper bearings output axial load	[N]	1220

Accessories





Hollow output shaft	AC 25
---------------------	-------

Electric motor


Size		80 A4
Poles		4
Power	[kW]	0.55

Electric motor configuration

Motor flange	B14
Terminal box position	X3




Hollow output shaft




69.99
69.971


25.021
25.000



Mounting positions



Terminal box position




0.23



← Oil quantity [litres]

Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	6.5
Electric motor [kg]	9.8

Gearing data

Axial module	1.7
Number of starts	1
Lead angle	3° 55'
Pressure angle	20°

Backdriving

Static self-locking
Slow back-driving in case of vibrations
Low dynamic back-driving